



Pall Corporation



SeptraSol™ Plus

Liquid/Gas Coalescers

Filtration. Separation. Solution.™

FCSEPRASENa



SeptraSol™ Plus

Liquid/Gas Coalescers

Introduction

The **SeptraSol** Plus Liquid/Gas Coalescer removes liquids and solids from high flow gas streams that contain high concentrations of liquids.

Pall Corporation's staff of research scientists and engineers have designed these coalescers that change the way gas streams are conditioned.

The **SeptraSol** Plus media can process several times more liquid per unit area of media than conventional media and often eliminates the need for upstream bulk separation equipment such as mist eliminators and vane separators.

The **SeptraSol** Plus media is supplied in a large flow, high performance 6-inch diameter cartridge that can economically treat large gas flows in applications that require a high degree of protection from both solids and liquids including:

- Protecting compressors and turbines
- Removing lubrication oil, water, and compressor wear products from effluent gas streams
- Removing liquid aerosols from gases fed to amine sweetening and dehydration units to prevent foaming problems
- Protecting desiccant and catalyst beds
- Minimizing solution losses downstream of gas purification process units
- Cleaning dirty fuel gas to protect low Nox burners and fuel injection nozzles
- Controlling injection well plugging during gas flooding

Description

Liquid Influent Concentration – the key to coalescer performance

One major reason why coalescers do not function properly in the field is because of an underestimation of the liquid influent concentration to the coalescer. Simply stated, the more liquid charged to a coalescer system, the more coalescer media required. If the coalescer is challenged with too much liquid, significant quantities of liquid will become re-entrained in the effluent gas, and downstream equipment problems will continue to occur.

The **SeptraSol** Plus media is able to handle high levels of liquid per unit area and requires significantly fewer cartridges to remove liquid and solids from gases. This is illustrated in Figure 1, which compares the **SeptraSol** Plus liquid/gas coalescer with a conventional media pack. As the liquid load is increased, the number of cartridges required to remove the liquid also increases.

With conventional media packing, the cartridge requirement may become uneconomical once the liquid concentration gets above a few hundred ppmw. The **SeptraSol** Plus liquid/gas coalescer economically removes liquids from gas streams with high liquid loading, often eliminating the need for an upstream bulk separator.

Features, Advantages and Benefits of the Pall SeptraSol Plus Liquid/Gas Coalescers

Features	Advantages	Benefits
SeptraSol Plus media pack	• High liquid removal per unit area • Fewer elements needed • Minimized vessel diameter	• Reduced need for an upstream bulk separator • Reduced capital and installation costs
High-capacity large diameter element	• Fewer elements needed for a given gas flow rate • Minimized vessel diameter	• Reduced capital and installation costs • Smaller space required for installation
Patented Oleophobic/Hydrophobic media treatment	• Quicker liquid drainage • Lower saturated pressure drop • Quicker recovery from liquid slugs • Minimized vessel diameter due to less restrictions on annual velocity	• Reduced capital and operating costs • Improved product quality and consistency
High-effective filtration area	• Fewer element changeouts needed • High solids removal efficiency	• Lower operating and maintenance costs
High-efficiency media and equipment	• Consistently high liquid removal efficiency • Reduced liquid losses • Optimum protection of downstream equipment	• Lower maintenance costs and availability

SepraSol™ Plus

Liquid/Gas Coalescers

Coalescer Technical Information

The SepraSol Plus Liquid/Gas Coalescer – no longer just for polishing

Before the development of the **SepraSol** Plus liquid/gas coalescer, high-efficiency liquid/gas coalescers were used specifically for polishing.

Generally, if the liquid influent concentration was greater than a few hundred ppmw, a bulk separator such as a knock-out drum, mist eliminator, or vane separator was required upstream of the coalescer to remove large liquid droplets and a coalescer would be used to remove the small droplets (less than 5 micron).

As demonstrated below in Figure 1, the **SepraSol** Plus liquid/gas coalescer can handle high liquid loads, often eliminating the need for upstream bulk removal equipment. In addition to the benefits of our media, the **SepraSol** Plus liquid/gas coalescer also includes features that have been Pall coalescer standards for many years.

Oleophobic/hydrophobic Treatment

All of Pall's SepraSol and SepraSol Plus liquid/gas coalescers receive the patented oleophobic/hydrophobic treatment. Chemically treating the coalescer lowers the surface energy of the media and promotes rapid drainage of the coalesced liquids. This significantly increases the amount of liquid per square foot of media the coalescer can handle.

Added benefits to the chemical treatment include lower saturated pressure drop, which saves operating costs and rapid recovery from liquid slugs.

Figure 2 shows the effect of the benefits of both the oleophobic/hydrophobic treatment and the **SepraSol** Plus liquid/gas coalescer compared to a coalescer with conventional packing and no chemical treatment.

Note: under the process conditions stated, the **SepraSol** Plus liquid/gas coalescer with chemical treatment requires a significantly smaller assembly under maximum liquid loading conditions than the untreated coalescer with the conventional pack design. Assembly diameter is directly related to the overall installation cost.

Liquid Loading Comparison

Figure 1
Cartridge Requirement
Comparison of **SepraSol** Plus Liquid/Gas Coalescer Media Pack versus Untreated Conventional Media Pack





Figure 2
Assembly Diameter
Comparison of **SepraSol** Plus Media Pack versus Untreated Conventional Media Pack



SepraSol™ Plus

Liquid/Gas Coalescers

Technical Information

Nominal Cartridge Dimensions

Part Number	CS604LGH13 (single open end) CS604LGBH13* (single open end) CS604LGDH13 (double open end) CS604LGBDH13* (double open end)
Outer Diameter	152.4 mm (6")
Length	1016 mm (40")
Surface Area	2.6m ² (28 ft. ²)

* Amine compatible

Performance Specification

Solid Removal Rating*	99.7% @ ≥ 0.3µm
Liquid Removal Ratings	.01ppm downstream liquids (LASE)** 1 ppb downstream liquids (CAGI)*** 99.999% efficient at 0.3 micron (DOP)****
Temperature Rating	82°C (180°F) 65°C (150°F) with water
Clean and Saturated Pressure Drop	Sized to your specification

* Per sodium chloride challenge test

** Per the Pall Liquid Aerosol Separation Efficiency (LASE) Test

*** Per the modified ANSI/CAGI-400-1999 test procedure

**** Per the Di-Octyl Phthalate (DOP) test using a monodisperse 0.3 micron aerosol

Materials of Construction

- Resin bonded glass fiber **SepraSol** Plus coalescer media designed in a pack to handle large quantities of liquid
- Polymeric outer drainage layer to prevent liquid re-entrainment
- Oleophobic/hydrophobic treatment to improve liquid drainage, protect from liquid slugs and minimize saturated pressure drop
- Stainless steel metal support



Pall Corporation

Corporate Headquarters

25 Harbor Park Drive
Port Washington, NY 11050
+1 516 484 3600 telephone
+1 800 289 7255 toll free US

Portsmouth - UK

+44 (0)23 9230 3303 telephone
+44 (0)23 9230 2507 fax
processuk@pall.com

Visit us on the Web at www.pall.com

Pall Corporation has offices and plants throughout the world. For Pall representatives in your area, please go to www.pall.com/contact.

Because of technological developments related to the products, systems, and/or services described herein, the data and procedures are subject to change without notice. Please consult your Pall representative or visit www.pall.com to verify that this information remains valid.

© Copyright 2007, 2010, Pall Corporation. Pall, , and SepraSol are trademarks of Pall Corporation. ® Indicates a Pall trademark registered in the USA. *Filtration. Separation. Solution.SM* is a service mark of Pall Corporation.

Filtration. Separation. Solution.SM